




ANGLE FAUCET

TF Series Installation Instruction

Petunjuk Pemasangan Seri TF

INSTALLATION INSTRUCTION


■ ACCESSORIES CHECKING

LIST OF THE STANDARD ACCESSORIES:

Please double-check the accessory list here in after and contact our company or our distributor for any unconformity.


Remarks:

- 1. Without affecting their performance, accessories may be changed without further notice.
- 2. Drawings for reference only. Product size & shape refer to actual faucet.




Code	The Accessory List	Quantity
1	Main Body	1
2	Ring cap	1

Types of Handle:







■ Installation Instructions

- Do not disassemble the main body, as it has been installed & commissioned correctly & precisely before leaving the factory.
- To avoid the faucet from jamming, do flush the water pipe before installation.
- After installation, make sure every joint safely sealed & no leaking.



■ Installation Procedures


- Make sure the installation holes to be in right size.
- Connect the main body & water supply pipe with water inlet pipe.




■ Usage

How to operate the handle:

- Rotate the handle 90° to turn on the water and turn it back to turn the water off.



■ Cleaning & Maintenance



To keep the product clean & shining, follow the steps as below:

- Flush with clean water & dry with soft cloth only.
- If any dirt, clean with soft liquid or transparent glass detergent.
- Do not use any scrubbing detergent, polisher, sand-cloth, paper tissue or scraper.
- Do not use acid detergent, indissolvable grain-like detergent or soap.



PETUNJUK PEMASANGAN


■ PENGECEKAN AKSESORIS

DAFTAR AKSESORIS STANDAR:

Harap lakukan pengecekan ulang terhadap kesesuaian aksesoris dengan daftar yang ada, jika terjadi ketidaksesuaian silakan hubungi kantor atau distributor kami.


Catatan:

- 1. Aksesoris mungkin akan diganti tanpa pemberitahuan lebih lanjut, tanpa memengaruhi performa produk.
- 2. Gambar yang tertera hanya sekedar referensi. Ukuran dan bentuk produk mengacu pada produk yang sebenarnya.




Kode	Daftar Aksesoris	Jumlah
1	Main Body	1
2	Karet seal	1

Jenis-jenis pegangan:




■ Petunjuk Pemasangan

- o Dilarang membongkar badan utama kran, karena telah dipasang dengan benar dan tepat sebelum kran keluar dari pabrik.
- o Untuk menghindari terjadinya kebuntuan pada kran, siram pipa air terlebih dahulu sebelum pemasangan.
- o Setelah terpasang, pastikan setiap sambungan telah disegel dengan aman dan tidak bocor.




■ Prosedur Pemasangan


- o Pastikan lubang pemasangan telah sesuai dengan ukuran yang ada.
- o Sambungkan badan utama dan pipa saluran air ke pipa saluran masuk.




- ① Pasang karet seal pada body kran



- ② Tempelkan plester pada insert dart agar menghindari terjadinya kebocoran



- ③ Pasang kran ke dinding dengan ukuran lubang yang sesuai




- ④ Eratkan karet seal

■ Penggunaan

Cara menggunakan pegangan kran:

- o Putar pegangan kran 90° untuk menyalakan air dan putar kembali pegangan kran ke tempat semula untuk mematikan air.



■ Pembersihan dan Perawatan



Untuk menjaga produk tetap bersih dan mengkilap, ikuti langkah-langkah di bawah ini.

- o Siram dengan air bersih dan keringkan dengan kain lap yang lembut.
- o Jika terdapat kotoran, bersihkan dengan cairan yang tidak keras atau dengan deterjen kaca transparan.
- o Jangan menggunakan deterjen gosok, penggosok, kertas tisu, atau pengikis/pengikir.
- o Jangan menggunakan butiran dengan zat kimia yang sulit larut seperti deterjen dan sabun.





www.aer.co.id